Instruction Sheet for Downdraft Door Replacement kit

NOTE: A short Video of the process is available on servicematters.com. Search JID4436ES0.

Kit Contains:

Downdraft Door Downdraft Door Support Plate Tube of Silicone Alcohol Wipes Instruction Sheet

 Remove the old downdraft door assembly by opening the door and prying off with a small screw driver. See Figure 1.



FIGURE 1

 Clean the new surfaces to be glued on the downdraft door and the downdraft door support plate with the alcohol wipes and a lint-free cloth in order to avoid any contamination of grease, oil, dust, water, old adhesives/sealants. Let dry for 1 minute. See Figure 2.



FIGURE 2

Insert the downdraft door support plate pins into the frame of the door opening. See Figure 3.




FIGURE 3

Tools Needed:

- Caulking Gun
- Small Screwdriver

 Apply silicone to the center of the downdraft door support plate keeping it away from the sides edges as illustrated. See Figure 4.



FIGURE 4

 Apply the downdraft door with the logo up and facing you as illustrated applying slight pressure downward making sure that the gaps are the same and the cover sits flush. See Figure 5.

IMPORTANT: If the downdraft door does not sit flush remove and apply more silicone to the low areas and repeat.

NOTE: Allow unit to dry for 24 hours before use.



FIGURE 5

Universal Keywords: Div22 Src664 Whirlpool Mechtech

Document Specific Keywords: Instruction Sheet

Date: 112116

Document Name: W11028611A

Subject: Whirlpool JennAir Downdraft Cooktop Door Replacement Kit Instructions

Models: W11028611 JID4436ES0