

# SEARS Instruction Sheet

## ROOF RACK MOUNTING WITH UNIVERSAL QUICK RELEASE KIT

*Sport 20-SV* Model 300.72000 (20 cu.ft.)

### Quick Release Contents

DESCRIPTION	PART NO.	QUAN
<b>Quick Release Kit</b>	<b>04851</b>	<b>1</b>
Saddle Quick Release		4
Interior Plate - 5 Hole		4
Reinforcing Plate		4
Carriage Bolt		8
Threaded Knobs		8
Mask, Vinyl Hole Covers	10 tabs	
Instruction Sheet		1

### MOUNTING INSTRUCTIONS

1. Place carrier on vehicle's roof rack. Adjust roof rack crossrails so they are positioned between the desired pre-drilled holes on the carrier bottom.
2. Remove carrier from vehicle's roof rack crossrails. Assemble the saddle assembly on carrier bottom as shown in Figure 1, using the desired pre-drilled holes. Turn the threaded knobs clockwise just enough to engage the threaded ends of the carriage bolts. Leave the assembly loose.

### IMPORTANT-READ BEFORE MOUNTING CARRIER TO VEHICLE

Before installing the carrier, carefully read the guidelines for use of the carrier. Proper installation of the carrier is the customer's responsibility. The manufacturer's warranty is limited to the repair or replacement of a defective carrier. Damage to the vehicle, the carrier's contents, or to any person or property is excluded.

The Sport 20-SV carrier can only be mounted to roof racks with a capacity of 150 pounds or more. See application chart on store display for approved factory installed roof racks. No more than 100 pounds of evenly distributed weight should ever be transported in the carrier.

1. Consult the vehicle owner's manual or the vehicle dealership for the weight capacity of factory installed roof racks.
2. If using an aftermarket roof rack consult the manufacturer of the roof rack for weight capacity.

Do not travel with an empty carrier at speeds over 40 MPH. Keep a minimum of 50 pounds in the carrier at high speeds to avoid undesirable wind effects. It is recommended to remove carrier from vehicle when not in use.

All carrier hardware should be firmly attached. When traveling periodically check all hardware to assure it is fastened securely. The carrier is water resistant, not waterproof. Always protect contents accordingly.

DO NOT place valuable or fragile items in the carrier. Sudden stops may cause contents to shift, possibly damaging items. The carrier is not designed to be accident or theft proof. The manufacturer and retailer cannot be held responsible for damage or theft of carrier's contents.


### LIMITED WARRANTY

The Sport 20-SV warranty is limited to (1) year from the date of purchase which include defects in material and workmanship. Manufacturer's warranty obligation is at manufacturer's sole discretion upon inspection of the carrier.

**Lost Keys:** If replacement or additional keys are needed, call 1-800-527-7483 with the three digit number stamped on the lock. Two keys will be mailed to you for \$5.00. Allow two weeks for delivery


Save this Instruction sheet for future reference. If additional or replacement Quick Release Kit is needed for carrier refer to carrier model number and part number. Replacement parts are available through Sears Parts Department, 800-366-7278

Figure 1




3. When you are ready to mount the carrier to the vehicle's roof rack crossrails, slide each saddle until it separates from the carriage bolt and drops down as shown in Figure 2.

Figure 2



4. Position saddles under the crossrails and push the saddle back over the carriage bolt and slide it forward until it stops. Turn knobs clockwise and tighten equally and securely as shown in Figure 3.

Figure 3



5. To remove carrier from roof rack, loosen knobs, slide saddles until they separate from carriage bolts. Slide carrier forward and lift off of vehicle. Leave all the parts attached to your carrier to simplify your next installation.
6. Place Vinyl Mask Hole covers over remaining holes in carrier bottom to prevent water or dirt entering the carrier.