

Installation Instructions

30" Electric Slide-In Ranges

Questions? Call 1 800 GE CARES (1 800 432.2737) or visit www.GEAppliances.com
 In Canada call 1.800.561.3344 or visit www.GEAppliances.ca

BEFORE YOU BEGIN

Read these instructions completely and carefully.

- **IMPORTANT** — Save these instructions for local installer's use
- **IMPORTANT** — Observe all governing codes and ordinances.
- **Note to Installer** — Be sure to leave these instructions with Consumer.

Note to Consumer — Keep these instructions for future reference.

Skill level — Installation of this appliance requires basic mechanical skills and advanced electrical skills.

Proper installation is the responsibility of the installer.

Product failure due to improper installation is not covered under Warranty.

FOR YOUR SAFETY:

WARNING — Before beginning the installation, switch power off at service panel and lock the service disconnect means to prevent power from being switched on accidentally. When the service disconnecting means cannot be locked, securely fasten a prominent warning device, such as a tag, to the service panel.

All ranges can tip. BURNS or other SERIOUS INJURIES can result. INSTALL and CHECK the ANTI-TIP bracket following the instructions supplied with the bracket.

Anti-Tip Bracket Kit Included

If you did not receive an anti-tip bracket with your purchase, call 1 800.626.8774 to receive one at no cost. (In Canada, call 1 800.561.3344.) For installation instructions of the bracket, visit: www.geappliances.com. (In Canada: www.geappliances.ca)

MATERIALS YOU MAY NEED

Squeeze Connector (For Conduit Installations Only)

UL Listed 40 AMP 4-Wire Cord 4' long OR 3-Wire Cord 4' long

TOOLS YOU WILL NEED

Drill with 1/8" Bit
Tin Snips
Safety Glasses
Tape Measure
Adjustable Wrench
Pliers
Level
1/4" Nut Driver

1 REMOVE PACKAGING MATERIALS:

Failure to remove packaging materials could result in damage to the appliance. Remove all packing parts from oven, racks, heating elements and drawer. Also, remove protective film and labels on the door, cooktop (do not remove side protection on glass cooktops) and backguard. Do not remove protective channel from sides of glass cooktop if applicable until later in installation.

6 POWER CORD AND CONDUIT INSTALLATION (CONT.)

C For power cord installations only (see the next step if using conduit), assemble the strain relief in the hole. Insert the power cord through the strain relief and tighten. Allow enough slack to easily attach the cord terminals to the terminal block. If tabs are present at the end of the winged strain relief, they can be removed for a better fit.

NOTE: Do not install the power cord without a strain relief. The strain relief bracket MUST be installed before reinstalling the rear range wiring cover.

D For conduit installations only, purchase a squeeze connector matching the diameter of your conduit and assemble it in the hole. Insert the conduit through the squeeze connector and tighten. Allow enough slack to easily attach the wires to the terminal block.

NOTE: Do not install the conduit without a squeeze connector. The squeeze connector MUST be installed before reinstalling the rear range wiring cover.

7 3-WIRE INSTALLATION

WARNING: The neutral or ground wire of the power cord must be connected to the neutral terminal located in the center of the terminal block. Ground strap must connect the neutral terminal to the ground plate. The power leads must be connected to the lower left and the lower right terminals of the terminal block.

DO NOT REMOVE the ground strap connection

FOR POWER CORD INSTALLATION

A Remove the 3 lower terminal screws from the terminal block.

B Insert the 3 terminal screws through each power cord terminal ring and into the lower terminals of the terminal block. Be certain that the center wire (white/neutral) is connected to the center lower position of the terminal block.

C Tighten screws securely into the terminal block.

FOR CONDUIT INSTALLATION

A Loosen the 3 lower terminal screws from the terminal block.

B Strip wire to expose tip about 5/8" long. Insert the center (white/neutral) wire tip through the bottom center terminal block opening. On certain models, the wire will need to be inserted through the ground strap opening and then into the bottom center block opening. Insert the two side bare wire tips into the lower left and the lower right terminal block openings.

C Tighten screws until the wire is firmly secured (35 to 50 inch-lbs). Do not over-tighten the screws.

NOTE: ALUMINUM WIRING: Aluminum building wire may be used but it must be rated for the correct amperage and voltage.

PROCEED TO STEP 9.

2 PREPARE THE OPENING (FOR INDOOR USE ONLY)

If the countertop area is not flat, excess tension may be applied to the glass cooktop causing breakage and voiding the warranty. Make sure the wall covering, countertop, flooring and cabinets around the range can withstand the heat (up to 200°F) generated by the range.

A Allow 30" minimum clearance between surface units and bottom of unprotected wood or metal cabinet or allow a 24" minimum when bottom of wood or metal cabinet is protected by no less than 1/4" thick flame resistant material covered with no less than No. 29 HSG sheet metal (315" thick). 915" thick stainless steel, 025" aluminum or 020" copper.

B This appliance has been approved for 0" spacing to adjacent surfaces above the cooktop. However a minimum 6" spacing to surfaces less than 15" above the cooktop and adjacent cabinetry is recommended to reduce exposure to steam, grease splatter and heat. Allow 1/4" minimum clearance at the back wall.

To reduce the risk of burns or fire when reaching over hot surface elements, cabinet storage space above the cooktop should be avoided. If cabinet storage space is to be provided above the cooktop, the risk can be reduced by installing a range hood that projects at least 5" beyond the front of the cabinets. Cabinets installed above the cooktop must be no deeper than 13".

NOTE: Use a 4' power cord to prevent interference with the storage drawer. Power cords 4'-7\"/>

3 ALTERNATE INSTALLATION / CONSTRUCTION KITS

Description: Backguard Kit: Adds a decorative backguard to the rear of the range. This kit can only be used when the opening in the countertop is 25\"/>

Use: Designed to be used when replacing a free-standing range with a slide-in.

Maintop Filler Kit: Adds a filler strip to the rear of the range. This kit can only be used when the opening in the countertop is 25\"/>

Use: Used to fill gap between the range back and wall.

Body Side Kit: Contains a color-matched side panel which can be used to create a finished appearance on either side of the range.

Use: Designed to be used when cabinets are absent on one side of the range of the range.

Lower Trim Kit: Contains a color-matched toe kick and extra-long leveling legs. Designed to be used when the range needs to be raised higher than 36-1/2\"/>

Use: Use kit when countertop height is 36-1/2\"/>

To order accessory kits, call 1 866 775-4557 or visit www.GEAppliances.com.

4 PREPARE THE RANGE

STORAGE DRAWER REMOVAL

A Pull drawer out until it stops.
 B Lift front of drawer until the stops clear the guide.
 C Pull forward and remove the drawer.

DOOR REMOVAL (optional)

Door removal is not a requirement for installation of the product but is an added convenience. To remove the door:

A Open the oven door as far as it will go.
 B Push both hinge locks down toward the door frame to the unlocked position. This may require a flat-blade screwdriver. **DO NOT LIFT THE DOOR BY THE HANDLE!**
 C Place hands on both sides of the door, and close the oven door to the removal position. (Approximately 1\"/>

D Lift door up and out until the hinge arms clear the slots.

NOTE: The oven door is very heavy. Be sure you have a firm grip before lifting the oven door off the hinges. Use caution once the door is removed. Do not lay the door on its handle. This could cause dents or scratches.

5 ELECTRICAL REQUIREMENTS

WARNING: This appliance must be properly grounded.

WARNING: All new constructions, mobile homes, recreational vehicles and installations where local codes do not allow grounding through neutral require a 4-conductor UL-listed range cord.

WARNING: To prevent fire or shock, do not use an extension cord with this appliance.

WARNING: To prevent shock, remove house fuse or open circuit breaker before beginning installation.

We recommend you have the electrical wiring and hookup of your range connected by a qualified electrician. After installation, have the electrician show you how to disconnect power from the range. You must use a single-phase, 120/208 VAC or 120/240 VAC, 60 hertz electrical system. If you connect to aluminum wiring, properly installed connectors approved for use with aluminum wiring must be used.

Effective January 1, 1996, the National Electrical Code requires that new construction (not existing) utilize a 4-conductor connection to an electric range. When installing an electric range in new construction, mobile home, recreational vehicle, or an area where local codes prohibit grounding through the neutral conductor, refer to the section on four-conductor branch circuit connections. Check with your local utilities for electrical codes which apply in your area. Failure to wire your oven according to governing codes could result in a hazardous condition. If there are no local codes, your oven must be wired and fused to meet the National Electrical Code, NFPA No. 70 - latest edition, available from the National Fire Protection Association.

This appliance must be supplied with proper voltage and frequency and connected to an individual, properly grounded 40 amp (minimum) branch circuit protected by a circuit breaker or time-delay fuse.

Use only a 3-conductor or a 4-conductor UL-listed range cord. These cords may be provided with ring terminals on wire and a strain relief device.

A range cord rated at 40 amps with 125/250 minimum volt range is required. A 50 amp range cord is not recommended, but if used, it should be marked for use with nominal 1 1/2\"/>

The rating plate is located on the oven frame or on the side of the drawer frame.

6 POWER CORD AND CONDUIT INSTALLATION

A Remove wire cover (on the back of range) by removing screws using a 1/4\"/>

DO NOT discard these screws.

B For power cord and 1\"/>

Terminal block (appearance may vary)

Knockout ring in bracket

Knockout ring removed

8 4-WIRE INSTALLATION

WARNING: The neutral wire of the supply circuit must be connected to the neutral terminal located in the lower center of the terminal block. The power leads must be connected to the lower left and the lower right terminals of the terminal block. The grounding lead must be connected to the frame of the range with the ground plate and the green ground screw.

FOR POWER CORD INSTALLATION

A Remove the 3 lower terminal screws from the terminal block. Remove the ground screw and ground plate and retain them. Cut and discard the ground strap. **DO NOT DISCARD ANY SCREWS.**

B Insert the one ground screw into the power cord ground wire terminal ring, through the ground plate and into the frame of the range.

C Insert the 3 terminal screws (removed earlier) through each power cord terminal ring and into the lower terminals of the terminal block. Be certain that the center wire (white/neutral) is connected to the center lower position of the terminal block. Tighten screws securely into the terminal block.

FOR CONDUIT INSTALLATION

A Loosen the 3 lower terminal screws from the terminal block. Remove the ground screw and ground plate and retain them. Cut and discard the ground strap. **DO NOT DISCARD ANY SCREWS.**

B Strip the wire to expose tip about 5/8\"/>

C Tighten the screws until the wire is firmly secured (35 to 50 inch-lbs). Do not over-tighten the screws.

NOTE: ALUMINUM WIRING: Aluminum building wire may be used but it must be rated for the correct amperage and voltage.

10 ANTI-TIP DEVICE INSTALLATION

WARNING: All ranges can tip. BURNS or other SERIOUS INJURIES can result. INSTALL and CHECK the ANTI-TIP bracket following the instructions supplied with the bracket.

The bracket should stop the range within 4 inches. If it does not, the bracket must be reinstalled. If the range is pulled from the wall for any reason, always repeat this procedure to verify the range is properly secured by the anti-tip bracket. Never completely remove the leveling legs or the range will not be secured to the anti-tip device properly.

11 SLIDE RANGE INTO OPENING

A Position the range in front of the cabinet opening. Make sure that the glass that overhangs the countertop clears the countertop. If necessary, raise the unit by lowering the leveling legs.

B Push while fitting the range into the opening, until the range is within 2\"/>

C Using the adjustable pliers or wrench, carefully screw in the back leveling leg until the glass overhang comes to rest on the countertop. Then carefully screw in the front two leveling legs until the glass overhang touches the countertop.

D Carefully push the range into the opening until the countertop fully engages the control panel. The back glass overhang should cover the cutout opening. Plug the range cord into the receptacle. Locate the cord in the back of the range in a manner that it will not touch or be moved by the drawer.

12 REPLACING THE OVEN DOOR

NOTE: The oven door is heavy. You may need help lifting the door high enough to slide it into the hinge slots. Do not lift the door by the handle.

A Lift the oven door by placing one hand on each side. The door is heavy, so you may need help. Do not lift the door by the handle.

B With the door at the same angle as the removal position (approximately 1\"/>

C Fully open the door. If the door will not fully open, the indentation is not seated correctly in the bottom edge of the slot.

D Push the hinge locks up against the front frame of the oven cavity to the locked position.

E Close the oven door.

Bottom edge of slot
Hinge arm
Hinge in locked position
Notch of hinge securely fitted into bottom of hinge slot
Hinge notch

13 FINAL INSTALLATION CHECKLIST

- Check to make sure the circuit breaker is closed (RESET) or the circuit fuses are replaced
- Be sure power is in service to the building
- Check that all packing materials and tape have been removed. This will include tape on metal panel under control knobs (if applicable), adhesive tape, wire ties, cardboard and protective plastic. Failure to remove these materials could result in damage to the appliance once the appliance has been turned on and surfaces have heated.
- Check that the door and drawer are parallel to each other and that both operate smoothly. If they do not, see the Owner's Manual for proper replacement.
- Check to make sure that the rear leveling leg is fully inserted into the anti-tip bracket and that the bracket is securely installed.

OPERATION CHECKLIST

- Turn on one of the surface units to observe that the element glows within 60 seconds. Turn the unit off when glow is detected. If the glow is not detected within the time limit, check the range wiring connections. If change is required, reset again. If no change is required, have building wiring checked for proper connections and voltages.
- Check that the oven control operates properly. If the oven control does not operate properly, check the wiring connections.
- Be sure all range controls are in the OFF position before leaving the range.

