



RT50-R Retro Scooter Set up Instructions

Removal from Crate




1. Remove cardboard carton from metal frame.




2. Remove scooter and parts provided for assembly from carton.

Parts and Hardware




Handlebar




Handlebar assembly

Steering stem



Bolt


Nut



3. Attach handlebar assembly to steering stem using hardware provided. Torque bolt to 33 ft.lbs.




Electrical components




Zip tie

4. Connect electrical components and secure all wires with zip tie.

Front wheel



5. Align speed sensor between front wheel and front fork.






6. Place front wheel spacer between disc brake and fork on axle bolt. Attach front wheel with axle nut provided. Torque to 33ft.lbs.

Axle nut

Brake hose

Clamp




7. Remove brake caliper shipping spacer and discard. Attach brake caliper to front forks using bolts provided. Torque bolts to 7 ft.lbs.


8. Secure brake hose using clamp on fork.

Headlight Panel


Headlight panel



9. Connect headlight wire.





Tab




10. Insert headlight panel to tabs on scooter and secure with 4mm phillip head screws.

Mirrors



11. Attach left and right mirrors to handlebars secure by tightening nut.

Rear Mud Flap








Mud flap

12. Attach rear mud flap to rear fender with 4mm phillip head screw.

Battery Installation

Battery located in floorboard.



▲ WARNING

The following procedure is very dangerous and should be performed with utmost care and attention. Wear protective eyewear, rubber gloves, and have water available should electrolyte come in contact with skin or eyes. **KEEP ALL CHILDREN AWAY FROM THE AREA WHILE THIS PROCEDURE IS BEING PERFORMED.**

POISON – CAUSES SEVERE BURNS

Contains sulfuric acid.

Avoid contact with skin, eyes, or clothing

To prevent accidents, rinse empty container with water.

ANTIDOTE:

External – flush with water

Internal – Call physician immediately. Drink large quantities of water or milk.

Follow with milk of magnesia, beaten eggs or vegetable.

Eyes – Flush with water for 15 minutes and get prompt medical attention.

KEEP OUT OF REACH OF CHILDREN.

Battery Installation

Note: The following page is for vehicles with battery's containing separate electrolyte pack. Most battery's will come with the electrolyte already sealed into the battery.

Preparing the battery:

- Place battery on level surface. Remove sealing tape from top. (see figure 20)
- Take the electrolyte container out of the plastic bag.
- Place electrolyte container upside down with the sealed silver mouths of the electrolyte bottles in line with the six filler holes of the battery. (see figure 21)
- Push the container down strongly enough to break the silver seals.
- As electrolyte starts flowing into battery, air bubbles will come up from the mouths of the plastic electrolyte bottles.
- Leave bottles upside down in battery holes until electrolyte is completely drained.
- Never leave children unattended around battery.
- If air bubbles cease to float to the top of the electrolyte bottles, tap lightly on top.
- **DO NOT** remove container from battery while it is draining.
- Never cut or pierce electrolyte container.
- After all the electrolyte has drained from the bottles into the battery, pull plastic electrolyte bottles gently out of the battery.
- Discard empty electrolyte bottles in a waste area that is inaccessible to children and animals.
- After filling let battery stand for at least 30 minutes before charging. This allows the electrolyte to penetrate plates for optimum performance and ensures longer battery life.
- After 30 minutes the battery is ready for its initial charge. Place cap strip loosely over the filling holes as shown in the picture. (see figure 22)




Figure 20




Figure 21




Figure 22

Battery Installation

How to Initially Charge the battery:

1. Connect the red positive (+) cable to the red positive (+) pole of the battery. (see figure 23)

2. Connect the black negative (-) cable to the black negative (-) pole of the battery. (see figure 24)

Note: The red positive (+) cable has a larger diameter than the black negative (-) cable.

3. Charging rate: Charge battery @ 0.7 Amps for 5 ~ 10 hours.

- After charging is complete, press down firmly with both hands to seat the caps. (Do not pound or hammer.) The battery is now sealed. (see figure 25)
- Locate battery compartment on scooter. The battery compartment is located under the floorboard. (see figure 26)
- Attach red positive (+) cable to positive (+) terminal on battery. Then attach black negative (-) cable to negative (-) terminal on battery.
-




Figure 23




Figure 24




Figure 25




Figure 26


▲ WARNING

NEVER REMOVE THE STRIP OF CAPS
NOR ADD ANY WATER OR ELECTROLYTE.

Gas and Oil

13. Fill engine with correct amount of oil. Refer to owners manual for oil types and quantity.

14. Fill gas tank as specified in owners manual. Fuel tank located under seat



Oil Plug.

15. Refer to owners manual for proper starting instructions.

!!WARNING!!

This engine may be shipped with packing oil. This oil should be drained and replaced with new oil as described in the owners manual. Never attempt to start engine without first replacing engine oil with proper amount and grade as described in the owners manual.